

Elcometer 4340 Motorised / Automatic Film Applicators



Elcometer 4340 Motorised Film Applicator

At a glance:

- 11 preset transverse speeds from 0.5 - 10cm per second
- Sample temperature control option
- Smooth aluminium table - much smoother than glass - for better repeatability
- Wide range of standard and high precision perforated and channelled vacuum tables
- Adjustable travel carriage with 'stop' at end of travel

Can be used in accordance with:
ASTM D 823-C

- **Interchangeable head attachments:**
Easily switched between film applicators
 - Spiral Bar Head Attachment
 - Standard Applicator Head Attachment
 - Combined Spiral/Standard Head Attachment
- **Durable and rugged:**
Sturdy rigid design to ensure minimal movement during film application. Up to 15 years of standard use.
- **Choice of bed:**
 - Standard flat table
 - Single channel vacuum table
 - Double channel vacuum table
 - Perforated vacuum table
- **Smooth & multiple concurrent tests:**
 - Use up to 3 film applicators simultaneously
 - Test up to 2 Leneta test charts simultaneously
 - Able to test up to 2 test areas on perforated tables

An essential machine for preparing a wide variety of product samples including paint, varnish, cosmetics, glue, etc, with total consistency and reproducibility on various substrates including contrast charts, sheet steel, plastic foils and glass. All Elcometer 4340 models have 11 pre-set speeds and adjustable stroke length with quick release system.

The Elcometer 4340 Motorised Film Applicators are versatile, rugged and precise. The rigid construction ensures a smooth, consistent application without the ridges often associated with film application.

The Elcometer 4340 range of motorised Film Applicators comes as one universal base with user selectable head attachments - allowing the flexibility to test using standard film applicators (filmographs), spiral bar coaters or using the combined attachment of both the film applicator and spiral bar attachment.

Each table is engineered to the highest flatness rating (up to five times flatter than glass), and can be supplied in a number of variations to meet your specific test requirements.

Film Application & Test Charts

For numerous products such as paint, ink, varnishes, glue and cosmetics, the reliability of many laboratory tests is directly related to the quality of the samples prepared from it.

It is absolutely essential that any measurements made on such coatings, whether for the purpose of describing their appearance or their physical properties (colour, gloss, hiding power, drying time, etc), are made on the basis of uniform and comparable samples with precisely controlled thickness.

In order to meet such specific demands, Elcometer has a wide range of high quality, high precision film applicators and motorised film applicators for greater repeatability and reproducibility when undertaking a large number of sample tests.

Elcometer also offer a wide range of Leneta Test Charts – the market standard – to meet all your specific requirements




TECHNICAL SPECIFICATION	
Dimensions	600 x 470 x 305mm (23.6 x 18.5 x 12.6")
Weight	29kg (64lb)
Part Number	Please refer to the table below
Packing List	Elcometer 4340 Motorised Film Applicator, power cable(s) and operating instructions.

Part Number	Voltage	Test Chart Clip	Standard Table	Vacuum Table			Heating Equipment	
				Perforated ^a	Single Channel ^a	Double Channel ^a	Temperature Bath ^b	Electrically Heated ^c
K4340M10-	110 – 240V	✓	✓					
K4340M11-	110 – 240V	✓	✓				✓	
K4340M12-	220 - 240V	✓	✓					✓
K4340M12-D	110V	✓	✓					✓
K4340M100	110 – 240V	✓		✓				
K4340M101	110 – 240V	✓			✓			
K4340M102	110 – 240V	✓				✓		
K4340M110	110 – 240V	✓		✓			✓	
K4340M111	110 – 240V	✓			✓		✓	
K4340M112	110 – 240V	✓				✓	✓	
K4340M120	220 – 240V	✓		✓				✓
K4340M120D	110V	✓		✓				✓
K4340M121	220 – 240V	✓			✓			✓
K4340M121D	110V	✓			✓			✓
K4340M122	220 – 240V	✓				✓		✓
K4340M122D	110V	✓				✓		✓

^a Vacuum pump supplied separately

^b 15 to 100°C (59 to 212°F). Supplied ready to be fitted with a temperature bath. Temperature bath is not supplied.

^c Ambient to 200°C (392°F)

ATTACHMENTS	
A range of applicator head attachments is available separately, allowing the user to select the most appropriate for their specific use and Standard (if applicable)	
	<p>Film Applicator Attachment Supplied with weight and hexagonal wrench For Models M10-, M100, M101, M102 KT004340N001 For Models M11-, M12-, M110, M111, M112, M120, M121, M122 KT004340N101</p>
	<p>Spiral Bar Coater Attachment Supplied with weights (x2), hexagonal wrench, rubber mat (x2) and zero bar For Models M10-, M100, M101, M102 KT004340N002 For Models M11-, M12-, M110, M111, M112, M120, M121, M122 KT004340N102</p>
	<p>Combined Film Applicator & Spiral Bar Coater Attachment Supplied with weights (x3), hexagonal wrench, rubber mat (x2) and zero bar For Models M10-, M100, M101, M102 KT004340N003 For Models M11-, M12-, M110, M111, M112, M120, M121, M122 KT004340N103</p>

VACUUM PUMPS <i>(Used to provide vacuum to the vacuum tables)</i>	
Vacuum Pump, UK 240V	KTUK4930M001
Vacuum Pump, EUR 220V	KT004930M001
Vacuum Pump, US 110V	KTUS4930M001

Related Products



Elcometer Film Applicators:

Elcometer offers a comprehensive range of film applicators which include:

- Baker Film Applicators
- Bird Film Applicators
- Casting Knife Film Applicators
- Doctor Blade Film Applicators
- Cube Film Applicators
- Micrometric Film Applicators



Elcometer 4360 & 4361

Elcometer 4360 & 4361 Spiral Bar Coatders:

Made of stainless steel and consisting of a cylindrical bar wound with stainless steel wire, these spiral bar coatders are used to apply a pre-determined thickness for coatings with high levelling characteristics.



Elcometer 4695

Elcometer 4695 Leneta Test Charts:

Elcometer supplies a wide range of Leneta Test Charts from plain white to those having different patterns of black and white.

ENGLAND

Elcometer Limited
Edge Lane
Manchester M43 6BU

Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SA
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

NETHERLANDS

Elcometer NL
Newtonlaan 115
3584 BH Utrecht

Tel: +31 (0)30 210 7005
Fax: +31 (0)30 210 6666
e-mail: nl_info@elcometer.com
www.elcometer.com

FRANCE

Elcometer Sarl
97 Route de Chécý
45430 BOU

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Ulmer Strasse 68
D-73431 Aalen

Tel: +49 (0)7361 52806 0
Fax: +49 (0)7361 52806 77
e-mail: de_info@elcometer.de
www.elcometer.de